



NOTES:

1. SIGN SHALL BE 0.125 MINIMUM THICKNESS.
2. WHEN USING AN OVERHEAD SYSTEM, SOLAR PANEL SHALL BE MOUNTED AT 15' ABOVE SURFACE ELEVATION ON THE TYPE II OR TYPE III SIGNAL POLE UNLESS OTHERWISE NOTED (I.E. ON THE MAST ARM) ON PLANS.
3. SOLAR HARNESS SHALL BE ORIGINAL EQUIPMENT FROM THE MANUFACTURER AND SIZED LONG ENOUGH SO THAT THERE ARE NO SPLICES IN THE CABLE.
4. POLE PENETRATIONS SHALL BE MADE AS SMALL AS PRACTICAL AND UTILIZE GROMMETS AND/OR CORD GRIPS AS APPROPRIATE TO PROTECT THE CABLE SHEATHING. EXCESS SPACE AROUND THE HOLES SHALL BE FILLED WITH RTV SEALANT.



RECTANGULAR RAPID FLASHING
BEACON SYSTEM (RRFB) OVERHEAD
MOUNTING DETAIL AND NOTES

CIVIL & UTILITY ENGINEERING

APPR. BY: PKR

DATE: 02.24

DRAWN BY: EY

DWG: TR9

CAD FILE: 2022_TR9_06_2024